



AT-LP120X

MANUAL DIRECT-DRIVE TURNTABLE (ANALOGUE & USB)

The next generation of the critically-acclaimed turntable.

The LP120XUSB is the next generation of the critically-acclaimed LP120USB, featuring a new, streamlined, design and improved features.

Product Highlights

- Direct-drive, DC servo motor.
- Fully manual operation.
- Adjustable dynamic anti-skate control.
- Selectable 33/45/78 RPM speeds.
- Convert records to digital files via the USB output.
- Professional anti-resonance, die-cast aluminum platter with felt mat.
- AT-HS6 universal 1/2" mount headshell and AT-VM95E Dual Magnet™ phono cartridge with 0.3 x 0.7 mil elliptical stylus.
- AT-VM95E cartridge is compatible with any VM95 Series replacement stylus, offering a wide choice of options for every budget and application.
- Balanced S-shaped tonearm with hydraulically damped lift control and lockable rest.
- Built-in switchable phono pre-amplifier for phono- or line-level output.
- Stroboscopic platter with speed indicator.
- Variable pitch control with quartz speed lock.
- Removable plug-type target light for easier cueing in low light.
- Damped base construction for reduced low-frequency feedback coloration.
- AC adapter handles AC/DC conversion outside of the chassis, reducing noise in the signal chain.



SRP: £245.00/€279,00 (inc. VAT)

Specifications

Turntable

Replacement Stylus	VM95 Series
Drive Method	Direct-drive
Type	Fully manual
Motor	DC servo-controlled
Speeds	33 1/3 RPM, 45 RPM, 78 RPM
Turntable Platter	Die-cast aluminium
Starting Torque	>1.0 kgf.cm
Braking System	Electronic brake
Wow and Flutter	<0.2% WRMS (33 RPM)
Signal-to-Noise Ratio	>50dB
Phono Pre-Amp Gain	36dB nominal, RIAA equalized
Output Level	Pre-amp "PHONO": 2.5mV nominal at 1kHz, 5cm/sec Pre-amp "LINE": 150mV nominal at 1kHz, 5cm/sec
USB Function	PC or Mac with an available USB port (USB1.1 or higher) Windows 7 or above, or Mac OS X or above A/D, D/A – 16-bit/44.1kHz or 48kHz USB selectable; Computer interface – USB 1.1 Compliant Windows 7 or above, or MAC OS X or above
Power Supply Requirements	115/230V AC, 60/50Hz
Power Consumption	3W
Dimensions	141,6 x 452 x 352 (H x W x Dmm)
Weight	8.0kg
Accessories Included	AT-VM95E phono cartridge AT-HS6 headshell 1.9 m (6.2') USB cable Dual RCA (male) to dual RCA (male) cable Dcounterweight Felt mat; Dust cover 45 RPM adapter

Specifications are subject to change without notice.

audio-technica